

Microsoft

98-388

Introduction to Programming Using Java
QUESTION & ANSWERS

Question: 1

HOTSPOT

You are writing a Java method named `safeRoot`. The method must meet the following requirements:

- Accept two `double` parameters `radicand` and `index`
- If `radicand` is negative and `index` is even, return `null`
- If `radicand` is negative and `index` is odd, return `-Math.pow(-radicand, 1 / index)`
- Otherwise, return `Math.pow(radicand, 1 / index)`

How should you complete the code? To answer, select the appropriate code segments in the answer area. NOTE: Each correct selection is worth one point.

Answer Area

```
public static double safeRoot(double radicand, double index) {  
    [ ] {  
        if (radicand >= 0) [ ] radicand, 1 / index);  
        if (index % 2 == 0) [ ]  
    }  
    [ ] {  
        [ ] {  
            return null;  
        }  
    }  
    [ ] {  
        return -Math.pow(-radicand, 1 / index);  
    }  
}
```

```

public static double safeRoot(double radicand, double index) {
    if (radicand >= 0)
        if (index % 2 == 0)
            return Math.pow(radicand, 1 / index);
    else if (index % 2 == 0)
    else if (radicand >= 0)
    else
        if (radicand >= 0)
        if (index % 2 == 0)
            return null;
    else if (index % 2 == 0)
    else if (radicand >= 0)
    else
        if (radicand >= 0)
        if (index % 2 == 0)
            return -Math.pow(-radicand, 1 / index);
}
}

```

Answer:

```

public static double safeRoot(double radicand, double index) {
    if (radicand >= 0)
        if (index % 2 == 0)
            return Math.pow(radicand, 1 / index);
    else if (index % 2 == 0)
    else if (radicand >= 0)
    else
        if (radicand >= 0)
        if (index % 2 == 0)
            return null;
    else if (index % 2 == 0)
    else if (radicand >= 0)
    else
        if (radicand >= 0)
        if (index % 2 == 0)
            return -Math.pow(-radicand, 1 / index);
}
}

```

Question: 2

HOTSPOT

You work as an intern Java programmer at Adventure Works. Your team lead asks you to create a method. The method must meet the following requirements:

- Accept an `int` array
- Check for duplicate values in the array
- Stop the outer loop as soon as a duplicate value has been detected and return `true`
- Return `false` if all values in the array are unique

How should you complete the code? To answer, select the appropriate code segments in the answer are

a. NOTE: Each correct selection is worth one point.

```

public static boolean duplicate(int[] array) {

    boolean isDuplicate = false;

    for (   x++) {

        for (int y = x + 1; y < array.length;  )

            if (array[x] == array[y])

                isDuplicate = true;

            if (isDuplicate)

                

        }

    return isDuplicate;

}

```

```

public static boolean duplicate(int[] array) {

    boolean isDuplicate = false;

    for (int x = 0; x < array.length - 1; x++) {
        for (int y = x + 1; y < array.length; y++) {
            if (array[x] == array[y]) {
                isDuplicate = true;
            }
        }
    }

    return isDuplicate;
}

```

Answer:

Yes

No

```
if (age >= 25) {  
    discount = 0.50;  
} else if (age >= 21) {  
    discount = 0.25;  
} else {  
    discount = 0.0;  
}
```



```
if (grade == "A") {  
    message = "Exceeds Standards";  
} else if (grade == "B") {  
    message = "Meets Standards";  
} else {  
    message = "Needs Improvement";  
}
```



```
if (gpa == 4.0) {  
    priority = 1;  
} else if (gpa >= 3.0) {  
    priority = 2;  
} else if (gpa >= 2.5) {  
    priority = 3;  
}
```



Answer:

Yes

No

```
if (age >= 25) {  
    discount = 0.50;  
} else if (age >= 21) {  
    discount = 0.25;  
} else {  
    discount = 0.0;  
}
```

```
if (grade == "A") {  
    message = "Exceeds Standards";  
} else if (grade == "B") {  
    message = "Meets Standards";  
} else {  
    message = "Needs Improvement";  
}
```

```
if (gpa == 4.0) {  
    priority = 1;  
} else if (gpa >= 3.0) {  
    priority = 2;  
} else if (gpa >= 2.5) {  
    priority = 3;  
}
```

Question: 4

HOTSPOT

You need to evaluate the following code. Line numbers are included for reference only.

```
01 public static int fee(char model) {
02     int price = 0;
03     switch (model) {
04         case 'A':
05             price = 50;
06             break;
07         case 'T':
08             price = 20;
09         case 'C':
10             price = 5;
11             break;
12         default:
13             price = 100;
14             break;
15     }
16     return price;
17 }
```

Use the drop-down menus to select the answer choice that answers each question based on the information presented in the code.

What is the return value when `model` has a value of 'A'?

- 5
- 20
- 50
- 100

What is the return value when `model` has a value of 'T'?

- 5
- 20
- 50
- 100

What is the return value when `model` has a value of 'C'?

▼
5
20
50
100

What is the return value when `model` has any other value?

▼
5
20
50
100

Answer:

What is the return value when `model` has a value of 'A'?

	▼
5	
20	
50	
100	

What is the return value when `model` has a value of 'T'?

	▼
5	
20	
50	
100	

What is the return value when `model` has a value of 'c'?

	▼
5	
20	
50	
100	

What is the return value when `model` has any other value?

	▼
5	
20	
50	
100	

Question: 5

HOTSPOT

You are writing a Java method.

The method must meet the following requirements:

- Accept a `String` array named `entries`
- Iterate through `entries`
- Stop the iteration and return `false` if any element has more than 10 characters
- Otherwise, return `true`

Answer Area

```
public boolean validateEntries(String[] entries) {  
    boolean allValidEntries = true;  
     (String entry  entries) {  
        if (entry.length() > 10) {  
            allValidEntries = false;  
              
        }  
    }  
    return allValidEntries;  
}
```

Answer Area

```
public boolean validateEntries(String[] entries) {  
    boolean allValidEntries = true;  
     (String entry  entries) {  
        if (entry.length() > 10) {  
            allValidEntries = false;  
              
        }  
    }  
    return allValidEntries;  
}
```

do
for
while

break;
continue;
goto;

instanceof

Answer:

```
public boolean validateEntries(String[] entries) {
```

```
    boolean allValidEntries = true;
```

```
    for (String entry : entries) {
```

```
        if (entry.length() > 10) {
```

```
            allValidEntries = false;
```

```
            break;
```

```
        }
```

```
    }
```

```
    return allValidEntries;
```

```
}
```